

# VIAVI T-BERD/MTS 4100-Series OTDR Modules

For T-BERD®/MTS-2000, -4000, -5800, CellAdvisor 5G and OneAdvisor-800 Platforms

VIAVI Solutions 4100-Series OTDR modules let field technicians rapidly, reliably, and cost-effectively install, turn up, and troubleshoot any optical network architecture—enterprise, metro, long-haul, and FTTx/access point-to-point

The OTDR modules' optical performance, combined with the complete suite of T-BERD/MTS, CellAdvisor 5G and OneAdvisor-800 platform testing features, ensures that testing is done right the first time.

Standard testing features include:

- Automatic macrobend detection
- Summary results table with pass/fail analysis
- Bidirectional OTDR analysis
- Fast-Report — onboard report generation
- Smart Link Mapper (SLM) icon-based map view of the fiber link
- SmartAcq perform a short and long pulse acquisition to improve measurement reliability
- SmartTEST Assistant guides users with an easy step by step process




**T-BERD/MTS-2000**  
one-slot handheld modular platform for testing fiber networks



**T-BERD/MTS-4000 v2**  
Two-slot handheld modular platform for testing fiber networks



**T-BERD/MTS-5800**  
Handheld test instrument for testing 10 G Ethernet and fiber networks



**CellAdvisor 5G**  
Cell site test solution



**OneAdvisor-800**  
All-in-One Cell-site Installation and Maintenance Test Solution

## Benefits

- Up to 45 dB dynamic range and 256,000 acquisition points
- PON-optimized to test through a 1x256 splitter
- Combined single-mode/multimode into one (quad)
- Single/dual/tri-wavelength versions with 1310/1550/1625/1650 nm
- Integrated CW light source and power meter
- Ready for Enterprise-SLM, FTTA-SLM, and FTTH-SLM intelligent optical application software
- Instantly detects traffic when connected to live fiber (except on live/filtered port)
- ITU Fiber type identification (G65x A, B, C and D) with water peak detection at 1383nm



## Specifications

General (typical at 25°C)	
Weight	0.35 kg (0.77 lb)
Dimensions (w x h x d)	128 x 134 x 40 mm (5 x 5.28 x 1.58 in)
Optical Interfaces	
Interchangeable optical connectors <sup>1</sup>	FC, SC, LC (PC or APC) and ST (PC)
Technical Characteristics	
Laser safety class (21CFR)	Class 1
Distance units	Kilometers, feet, and miles
Group index range	1.30000 to 1.70000 in 0.00001 steps
Number of data points	- Up to 128,000 for MM, QUAD, LA - Up to 256,000 for MA2, MA3, MP2
Distance measurement	
Mode	Automatic or dual cursor
Display range	0.1 up to 400 km
Cursor resolution	1 cm
Sampling resolution	4 cm
Accuracy	$\pm 0.5 \text{ m} \pm \text{sampling resolution}$ $\pm 1.10^{-5} \times \text{distance}$ (excluding group index uncertainties) for MA2, MA3, MP2  $\pm 1 \text{ m} \pm \text{sampling resolution}$ $\pm 1.10^{-5} \times \text{distance}$ for LA, MM and QUAD

Attenuation Measurement	
Mode	Automatic, manual, 2-point, 5-point, and LSA
Display range	1.25 to 55 dB
Display resolution	0.001 dB
Cursor resolution	0.001 dB
Linearity	$\pm 0.03 \text{ dB/dB} / \pm 0.05$ for LA
Threshold	0.01 to 5.99 dB in 0.01 dB steps
Reflectance/ORL Measurements	
Reflectance accuracy	$\pm 2 \text{ dB}$
Display resolution	0.01 dB
Threshold	-11 to -99 dB in 1 dB steps
Source <sup>2</sup> Power Meter (optional)	
CW source output power level	-3.5 dBm
Power level range (MM/SM) <sup>3</sup>	-3 to -30 / 0 to -55 dBm
Calibrated wavelengths (SM)	1310/1490/1550/1625/1650 nm
Calibrated wavelengths (MM) <sup>4</sup>	850/1300 nm
Measurement accuracy (SM)	$\pm 0.5 \text{ dB}$
Measurement accuracy (MM) <sup>5</sup>	$\pm 1 \text{ dB}$

OTDR Modules (typical at 25°C)						
	Central Wavelength <sup>6</sup>	RMS Dynamic Range <sup>7</sup>	Event Dead Zone <sup>8</sup>	Attenuation Dead Zone <sup>9</sup>	Network Type	Applications
MM	850/1300 $\pm 30$ nm	26/24 dB	0.8 m	4 m	Enterprise/FTTA	Multimode network qualification
Quad	850/1300 $\pm 30$ nm 1310/1550 $\pm 20$ nm	26/24 dB 37/35 dB	0.8 m 0.9 m	4 m	Enterprise/FTTA/ access/metro	Multimode and single-mode short- and medium-haul network qualification
LA	1310/1550/1650 $\pm 20$ nm	35/33/30 dB	1.5 m	6 m	FTTA/FTTH/access	Short-haul qualification FTTH drop-cable qualification/maintenance
MA2	1310 $\pm 20$ nm 1383 $\pm 3$ nm 1550 $\pm 20$ nm 1625 $\pm 10$ nm	40 dB 37 dB 40 dB <sup>10</sup> 38 dB	0.7 m 2 m 0.7 m 0.7 m	3 m 6 m 3 m 3 m	FTTA/access/metro	Short/medium-haul qualification Wireless fronthaul and backhaul Water peak detection at 1383 nm
MA3	1310 $\pm 20$ nm 1550 $\pm 20$ nm 1625 $\pm 10$ nm 1650 $+10/-5$ nm	43 dB 41 dB 41 dB 41 dB	0.7 m	3 m	FTTH/access/ metro/long-haul	Short/medium/long-haul qualification FTTH test up to 1x128 splitter
MP2	1310 $\pm 20$ nm 1550 $\pm 20$ nm 1625 $\pm 10$ nm 1650 $\pm 10$ nm	46 dB 45 dB 44 dB 42 dB	0.65 m	2.5 m	FTTH/long-haul/ very long-haul	Long haul/very long haul qualification FTTH test up to 1x256 splitter

1. ST for QUAD/MM only

2. Same wavelengths as the OTDR port. Not available on live port.

3. -2 to -50 dBm for Quad

4. Available on MM and Quad modules

5. Using a modal controller

6. Laser at 25°C and measured at 10  $\mu\text{s}$

7. The one-way difference between the extrapolated backscattering level at the start of the fiber and the RMS noise level, after 3 minutes averaging

8. Measured at  $\pm 1.5$  dB down from the peak of an unsaturated reflective event

9. Measured at  $\pm 0.5$  dB from the linear regression using a FC/UPC-type reflectance

10. Measured on optical fiber with Rayleigh parameter  $K(-82.01\text{dB} \pm 0.17\text{dB}$  at 1546 nm

## Ordering Information

Description	Part Number
<b>OTDR Modules</b>	
Multimode 850/1300 OTDR module	E4123MM
Multimode/single-mode 850/1300/1310/1550 nm OTDR module	E4146QUAD
LA 1310/1550 nm OTDR module	E4126LA
MA2 1310/1550 nm OTDR module with straight connector	E4126MA2-PC
MA2 1310/1383/1550 nm OTDR module with straight connector	E4138MA283-PC
MA3 1310/1550 nm OTDR module with angled connector	E4126MA3-APC
MP2 1310/1550/1625 nm OTDR module with straight connector	E4136MP2-PC

Description	Part Number
<b>Universal Optical Connectors (for MM and QUAD)</b>	
Straight	EUNIPCFC, EUNIPCSC, EUNIPCST
8° angled	EUNIAPCFC, EUNIAPCSC
<b>Universal Optical Connectors (for MA2, MA3 and MP2 modules)</b>	
Straight	EUSCADS, EUFCADS, EULCADS
8° angled	EUSCADS-APC, EUFCADS, EULCADS-APC

Additional part numbers are available, please contact your VIAVI sales representative.

For more information on T-BERD/MTS-2000, -4000 V2, -5800 and CellAdvisor 5G test platforms or individual modules, refer to their respective data sheets and brochures.

For more information about our SLM (Smart Link Mapper) OTDR applications, refer to this document: <https://www.viavisolutions.com/en-us/literature/smart-link-mapper-otdr-applications-promo-sheet-en.pdf>

## VIAVI Care Support Plans

### Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

For more Information: go to [viavisolutions.com/viavicareplan](https://www.viavisolutions.com/viavicareplan)

## Features

\*5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration
 BronzeCare	Technician Efficiency	Premium	✓	✓	✓		
 SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	✓*	✓



Contact Us **+1 844 GO VIAVI**  
(+1 844 468 4284)

To reach the VIAVI office nearest you, visit [viavisolutions.com/contact](https://www.viavisolutions.com/contact).

© 2020 VIAVI Solutions Inc.  
Product specifications and descriptions in this document are subject to change without notice.  
otdr20004000-ds-fop-tm-ae  
30168330 911 0220