

IFF-45TSL

MK XIIB/TACAN Bench Test Set

User Interface

Interfaces Supported	IEEE-488, RS232 and Ethernet (VXI-11)
	Windows PC based GUI provided

Modes of Operation

Transponder Testing	1, 2, 3/A, C, S, 4, 5
Interrogator Testing	1, 2, 3/A, C, S, 4, 5
DME/TACAN Testing	G/A, INV G/A, BG/A, BA/A, A/A, INV A/A
ADS-B In and Out	
GICB Decode	



- Hence, for a power setting of -85 dBm, the accuracy will be $+ [0.5 + 0.05 \times 5]$, or ± 0.75 dB, and for a power setting of -95 dBm, the accuracy will be $\pm [0.5 + 0.05 \times 15]$, or ± 1.25 dB.
- As per example above

Signal Generator

Frequency Range	
+/- 10 MHz from the actual band of 962 to 1213 MHz that is defined for DME/TACAN, 10 kHz resolution	
Output Amplitude Direct Port	
0.0 dBm to -110.0 dBm (into 50 Ω) in 0.1 dB increments	
Accuracy@ 25° \pm 5° C	
0.0 dBm to -80.0 dbm	± 0.5 dB
< -80.0 dBm to -100 dBm	$\pm [0.5 \text{ dB} + 0.05 \text{ dB per dB below } -80 \text{ dBm}]^1$
< -100.0 dBm	$\pm [1.5 \text{ dB} + 0.35 \text{ dB per dB below } -100 \text{ dBm}]^2$
Accuracy over full temp	
0.0 dBm to -80.0 dbm	± 1.0 dB
< -80.0 dBm to -100 dBm	$\pm [1.0 \text{ dB} + 0.10 \text{ dB per dB below } -80 \text{ dBm}]^2$
< -100.0 dBm	$\pm [3.0 \text{ dB} + 0.70 \text{ dB per dB below } -100 \text{ dBm}]^2$
Antenna Port	
30.0 dBm to -60.0 dBm (into 50 Ω) in 0.1 dB increments	
Accuracy @ 25° \pm 5° C	
Power \geq -30.0 dBm	± 1.0 dB
Power < -30.0 dBm	$\pm [1.0 \text{ dB} + 0.033 \text{ dB per dB below } -30 \text{ dBm}]^2$
Accuracy over full temp	
Power \geq -30.0 dBm	± 2.0 dB
Power < -30.0 dBm	$\pm [2.0 \text{ dB} + 0.066 \text{ dB per dB below } -30 \text{ dBm}]^2$

Signal Generator (continued)

Pulse Formats	
Transponder/Interrogator	1, 2, 3/A, C, S, National Secure Mode, Mode 5
Support for RTCA DO-181E and DO-260B; Support for AIMS 17-1000	
DME/TACAN	G/A, A/A, INVERSE G/A, INVERSE A/A, BEACON G/A, BEACON A/A
Pulse Position Deviations	
XPDR	$\pm 1 \mu\text{s}$
INT Non-Mode 5	$\pm 1 \mu\text{s}$
INT Mode 5	$\pm 0.25 \mu\text{s}$
Accuracy [XPDR/INT]	$\pm 10 \text{ ns}$
TACAN ³	$12 \pm 0.1 \mu\text{s}$
Accuracy [TACAN]	$\pm 100 \text{ ns}$
Pulse Width Deviations	
Transponder ⁴	Nominal $\pm 1.0 \mu\text{s}$ (fixed in Mode S-SPR)
Accuracy	$\pm 10 \text{ ns}$
Interrogator ⁴	Nominal $\pm 0.5 \mu\text{s}$
Accuracy	$\pm 10 \text{ ns}$
TACAN	0 to $5.5 \mu\text{s}$
Accuracy	$\pm 0.1 \mu\text{s}$
Pulse Amplitude	
XPDR/INT	6 to -15 dB
TACAN	5 to -15 dB
Interference Pulse Characteristics (1 or 2 pulses)	
Position	-1 to $400 \mu\text{s}$ relative to reference
Offset Range	
XPDR	-44 to $400 \mu\text{s}$
INT	-1 to $400 \mu\text{s}$
Accuracy	$\pm 10 \text{ ns}$
Interference Pulse Spacing (multiple pulse interference mode)	
Range	-44 to $400 \mu\text{s}$ relative to 1st Pulse (XPDR) -1 to $400 \mu\text{s}$ (Interrogator)
Max 2nd pulse position	$400 \mu\text{s}$ - 1st pulse position
Accuracy	$\pm 10 \text{ ns}$

3. Pulse overlap not allowed

4. Minimum pulse width is 200 ns

Signal Generator (continued)

Range Delay	
DME/TACAN	1 to 400.00 nmi in 0.01 nm steps. Optional offset of -1 nm.
Accuracy	0.02 nm or 0.0003% of simulated range
INT	0 to 400.00 nmi
Accuracy	±0.01 nmi
Diversity	
Timing (either channel)	0 to ±1 µs, ±10 ns accuracy
Echo	
Position	30 nmi ±0.2 nmi
Pulse Pair Spacing	Same as Reply
Amplitude	-15 to 6 dB, referenced to the nominal reply
Resolution	0.1 dB
Accuracy	±0.25 dB
Channel Signal Assignment	
Transponder Test	Top/Bottom
Interrogator Test	Sum/Difference
TACAN	Top/Bottom
Interrogation Generator	
Independent/Unique Interrogations 1-12	
Fixed Mode	SIF Mode: 1 to 10000 PRF
	Mode 5: 1 to 1200 PRF
	Mode S: 1 to 2500 PRF
	NSM: 1 to 3500 PRF (internal) 1 to 2500 PRF (external)
Double/Supermode	
Spacing between interrogations (slaved delay)	0 to 400 µs
Pair generation rate	1 to 400 PRF
Supermode interrogations	2 interrogations
Burst Mode	
Bursts/trigger	1 to 1000 or infinite
Interrogations/burst	1 to 2500
Interrogation rate (within a burst)	1 to 3800 PRF
Spacing between burst sequences	0.1 to 20 sec
Interlaced Mode	
Interlace ratio	1:1 to 1:63
Group rate	1 to 400 PRF

Signal Generator (continued)

Reply Generator	
Independent/Unique Replies	1 to 12
Data and Range	Individually configured
Selectable Modes	1,2,3/A,C,ACLA,ACLC,S,4,5
Selectable Efficiency	1 to 100%
Spectral Purity Residual Level	
Harmonics	Direct: <50 dBc
	Antenna: <40 dBc
Spurious (> modulation BW)	<60 dBc, 350 to 1800 MHz
Phase Noise	<80 dBc/Hz @ 100 kHz

Signal Receiver Measurements

Frequency Range	
1020 MHz to 1155 MHz	
Output Amplitude Direct Port	
Pulse Power Measurements	
25 ±5° C	Direct: 10 to 66 dBm: +0.5 dB
	Antenna: -40 to 30 dBm: +1 dB
	Resolution: 0.01 dB
-10° to 55° C	Direct: 10 to 66 dBm: +1 dB
	Antenna: -40 to 30 dBm: +2 dB
	Resolution: 0.01 dB
Pulse to Pulse Spacing	
XPDR/INT	
Non-Mode 5	±0.3 μs
Mode 5	±0.0625 μs
Accuracy	±10 ns
TACAN	±0.5 μs
Accuracy	±50 ns
Reply Delay	
Accuracy	±20 ns
Reply Delay Jitter	
Accuracy	±20 ns
Frequency	
Accuracy	±50 kHz

Signal Receiver Measurements (continued)

% Reply	
Range	0 to 100% for each interrogation type
Resolution	0.0125% (for sample size = 8000)
Sample Size	1 to 8000 interrogations

Specific Application

TACAN/DME

Ident	
Variable	10 sec to 65 sec
Alphanumeric Character	0 to 9 [A to Z]

Bearing	
Bearing Input Range	0° to 359.99° in 0.01° steps
Bearing Accuracy	±0.05°
Bearing Rate	-39° to 39° sec in 0.01° steps

Velocity	
Range	0 to 9999 Kts in 1 Kt steps
Accuracy	±0.001%

Squitter	
Range	0 to 8000 Hz
Accuracy	10 Hz or 2%, whichever is greater
Distribution	Compliant with ARINC 568 @ 2700 Hz

Main Reference Burst	
Adjustable Burst (all modes)	1, 2, -1 or -2
Selectable	On/Off
X Channel	12 pulse pairs
Y Channel	13 single pulses
A/A (all channels)	10 single pulses
Accuracy	±100 ns

Auxiliary Reference Burst	
Adjustable Burst (all modes)	1, 2, -1, or -2
X Channel	6 pulse pairs
Y Channel	13 single pulses
Accuracy	±100 ns

Specific Application (continued)

TACAN Modulation	
Range	0% to 39% in 1 Hz steps (15 Hz and 135 Hz separately adjustable)
Accuracy	±1%
Distortion	<5% of either tone
A/A Interrogation Rate	0 to 3999 Hz in 1 Hz steps
Reply Efficiency	0 to 100% in 1% steps

Crypto Appliqué Compatibility

AIMS 04-900A Option A - KIV-78 and QRTK6 NG
AIMS 04-900A Option B - KIV-77, KIV-79 and SIT-2010
KIV-6

Built-in Crypto Appliqué Function

NSM Internal Crypto Simulator (standard) Word A/B, C1 - C16
Mode 5 Internal Crypto Simulator (standard with options 1 and 3) As defined by the U.S. Navy Mode 5 Program Office

Interface Signals

Analog Signal Ports (programmable output)

2 Ports	
Programmable Sources	Various
Level	±1 V into 50 Ω

Trigger Out (front panel)

Programmable Source	TX timing ref, RX detection
Level	3.3 V logic

Trigger In (front panel)

Functions	Interrogation Trigger Reply Trigger
Level	3.3 or 5 V logic

Suppression Out

Amplitude into 2 KΩ	12 V to 80 V
Variable Pulse Width	0.25 to 300 μs

Suppression In

Amplitude	10 V to 80 V
Impedance	2.2 KΩ
Action	Inhibits response to incoming signal

General

Frequency/Time Reference	2.5 ppm composed of 1 ppm/year aging and 1 ppm accuracy over temp
External Reference Input	External 10 MHz Source
VSWR	Direct: 1.2:1 over frequency range
	Antenna: 2.5:1 over frequency range
Input Power	100-240 VAC, 50-60 Hz, 3 Amp fuse

Environmental

Temperature Range	-10° to 55° C (14° to 131° F)
Warm-up (for specified accuracy)	45 minutes

Physical Characteristics

Dimensions (w/o controller)	17.75" W x 4" H x 21.5" D (45 cm x 10 cm x 54.6 cm)
Weight	24 lbs (10 kg)

Test Set Certifications

UL
CE
DoD AIMS MK XIIB Level 1 and Level 2, Level IIB (pending)

Export Control and Warning

VIAVI Solution's military products are controlled for export under the International Traffic in Arms Regulations (ITAR). A license from the U.S. Department of State is required prior to the export of this product from the United States. This product may not be sold or proposed or offered for sale to certain countries including: Belarus, Burma, China, Cuba, Haiti, Iran, Liberia, Libya, North Korea, Somalia, Syria, Sudan, and Vietnam. See ITAR 126.1 for complete information.



Contact Us: +1 800 835 2352 | AvComm.Sales@viavisolutions.com. To reach the VIAVI office nearest you, visit viavisolutions.com/contact

© 2025 VIAVI Solutions Inc. Product specifications and descriptions in this document are subject to change without notice. Patented as described at viavisolutions.com/patents

IFF45TSL-ds-avi-nse-ae
30187483 903 0225